

FRONT LOAD WASHER SPECIFICATIONS



All models shown with Quantum® controls

Models	Front Load Washer	Front Load Washer
Available Controls	Quantum, MDC	Quantum, MDC, Coin Slide
Available Control Location	Front	Rear
Capacity - lb (kg)	21.5 (9.5)	21.5 (9.5)
Cylinder Volume - cu. ft. (liters)	3.42 (96.8)	3.42 (96.8)
Width - in (mm)	26 7/8 (683)	26 7/8 (683)
Depth - in (mm)	27 3/4 (704)	27 3/4 (704)
Height - in (mm)	44 3/8 (1126)	43 (1092)
Spin Speed G-Force (RPM)	440 (1200)	440 (1200)
Motor Size - HP (kw)	Variable Speed Induction 0.9 (0.67)	Variable Speed Induction 0.9 (0.67)
Water Consumption per Cycle - g (l)*	11.7 (44.3)	11.7 (44.3)
WF (Water Factor)	3.8	3.8
MEF (Modified Energy Factor)	2.98	2.98
Available Water Temperatures	3	3
Available Cycles*	Normal, Perm Press, Delicate	Normal, Perm Press, Delicate
Water Pressure - PSI (Bar)	20-120 (1.4/8.3)	20-120 (1.4/8.3)
Cycle Indicator Lights	Yes	Yes
Cylinder Finish	Stainless Steel	Stainless Steel
Available Colors	White, Stainless	White
Door Type (Solid/Window)	Window	Window
Available Electrical Requirements (Voltage/Hz/Ph - Breaker Size)	120/60/1 - 15 Amp	120/60/1 - 15 Amp
Net Weight - lb (kg)	270 (122)	253 (115)
Shipping Weight - lb (kg)	290 (132)	273 (124)
Shipping Width - in (mm)	29 (737)	29 (737)
Shipping Depth - in (mm)	32 3/4 (832)	32 3/4 (832)
Shipping Height - in (mm)	45 1/2 (1156)	45 1/2 (1156)
Available Agency Approvals	cULus	cULus

ADA Compliant

Note: Not all options are available for all models. Refer to the price list for the available models and options.

*Information provided applies to premier control offered by product class.