

VENDED STACK TUMBLE DRYER SPECIFICATIONS

| | | STT30 | STT45 |
|--|--------------------------|---|--|
| Control Option | | Gold, MDC | Gold, MDC |
| Dry Capacity - lb (kg) | | 2 @ 30 (13.6) | 2 @ 45 (20.4) |
| Filling Ratio - lb (kg) | | 20:1 = 33 (15.1) | 20:1 = 46 (21.1) |
| Width - in (mm) | | 31 1/2" (800) | 34 1/2" (876) |
| Depth - in (mm) | | 42 7/8" (1086) | 48 5/8" (1235) |
| Height - in (mm) | | 76 1/4" (1937) | 81 1/16" (2059) |
| Cylinder Diameter - in (mm) | | 30" (762) | 33" (838) |
| Cylinder Depth - in (mm) | | 26" (660) | 30" (762) |
| Cylinder Volume - cu. ft. (liters) | | 10.6 (301) | 14.8 (421) |
| Door Opening Size - in (mm) | | 22 5/8" (576) | 26 7/8" (683) |
| Airflow - cfm (liter/sec) | | 60 Hz: 400 (189) 50 Hz: 340 (160) | 60 Hz: 600 (283) 50 Hz: 500 (236) |
| Air Outlet Diameter - in (mm) | | 1 x 8" (203) | 1 x 10" (254) |
| Energy Data | | Gas Models: 146,000 Btu/hr (42.8 kW) total Steam Models: At 100 psi (6.9 bar): 3.2 BHP, 111,000 Btu/hr (32.5 kW) Electric Models: 21 kW | Gas Models: 190,000 Btu/hr (55.6 kW) total - 60Hz 174,000 Btu/hr (51.0 kW) total - 50 Hz |
| Electrical Specifications | | Gas and Steam Models: 120/208-240/60/1; 2W/3W+G 100/200-220/60/1; 2W+G 100/200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/240/60/3; 3W+G 380/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 380/400-415/50/3; 3W+G 460-480/60/3; 3W+G Electric Models: 200-208/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G* 240/60/3; 3W+G 380/60/3; 3W+G 380/50/3; 3W+G 400-415/50/3; 3W+G 460-480/60/3; 3W+G | Gas Models Only: 200/60/1; 2W+G 208-240/60/1; 3W+G 200-208/240/60/3; 3W+G 200/50/1; 2W+G 230-240/50/1; 2W+G |
| Motor Size - HP (W) | Fan Cylinder | 1/4 (187) 1/4 (187) | 1/2 (375) 1/2 (375) |
| Plumbing Connections | | Gas Models: 1/2" - NPT One manifold gas connection. Steam Models: 3/4" - NPT | Gas Models: 1/2" - NPT One manifold gas connection. |
| Shipping Dimensions Approx. - in (mm) | Width Depth Height | 32 1/2" (825) 47" (1194) 81" (2057) | 35 1/2" (902) 54" (1372) 85" (2159) |
| Net Weight - lb (kg) | | 544 (247) | 673 (305) |
| Shipping Weight - lb (kg) | | 582 (264) | 718 (326) |
| Agency Approvals | | Gas Models: CSA Star, CSA Flame, cCSAus, CE, Australia Gas Electrical & Steam Models: cCSAus, CE | Gas Models: CSA Star, CSA Flame, cCSAus, CE, Australia Gas |

*Not available in EU

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Speed Queen distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. Amperage ratings available in Installation Manual.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

speedqueen.com