TOP LOAD WASHER SPECIFICATIONS

	Quantum Gold	MDC (Micro-Display Control)	Electromechanical
Basket/Cylinder Volume - cu. ft. (liters)	3.26 (92)	3.26 (92)	3.26 (92)
Width - in (mm)	25 5/8" (651)	25 5/8" (651)	25 5/8" (651)
Depth - in (mm)	28" (711)	28" (711)	28" (711)
Height* - in (mm)	43 (1092)	43 (1092)	43 (1092)
Work Surface Height - in (mm)	36" (914)	36" (914)	36" (914)
Weight - lb (kg)	190 (86)	190 (86)	190 (86)
Shipping Weight - lb (kg)	210 (95)	210 (95)	210 (95)
Cycle Time - minutes	Programmable	16-31	16-31
Motor - HP	2-speed, 1/2 HP	2-speed, 1/2 HP	1-speed, 1/2 HP 2-speed, 1/2 HP
Water Consumption - gal. per cycle	27.3	27.4	27.3
Water Factor - gal. per cu. ft.	8.4	8.4	8.4
Modified Energy Factor (MEF)	1.75	1.70	1.65
Hot Water - gal. per cycle	1.9	2.4	2.3
Water Pressure - psi (bar)	Pressure fill – 20 to 120 (1.4/8.3)	Pressure fill – 20 to 120 (1.4/8.3)	Pressure fill – 20 to 120 (1.4/8.3)
Spin Speed - RPM	2-spd, High 710, Low 473	2-spd, High 710, Low 473	2-spd, High 710, Low 473
Cycle/Temperature	Hot Normal Warm Perm Press Cold Delicate	Normal Hot Normal Warm Perm Press Warm Delicates Cold	Hot Normal Warm Perm Press Cold Delicate
Electrical Specifications and Circuit Requirements	120/60/1-15 amp	120/60/1-15 amp	120/60/1-15 amp
Agency Approval	cULus	cULus	cULus
Activation	Coin/Card-Operated	Coin/Card-Operated	Coin/Card-Operated
Self-Adjusting Rear Legs	Yes	Yes	Yes
Top and Lid Finish	Porcelain	Porcelain	Porcelain
Colors	White, Bisque	White, Bisque	White, Bisque

* Heights may vary slightly depending on leveling adjustments.

At Speed Queen, we're so confident that our heavy-duty commercial washers and dryers are built for reliable performance, that we're offering the following limited warranty to prove it:
Through three years† — Any part of the washer, dryer or stack dryer. Through five years† — The washer transmission assembly, base and cabinet assembly including top, lid and door, against rust from inside out.
Lifetime — The stainless steel washtub.

† Parts only. Labor not included. See Speed Queen Warranty Bond for specifics.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice.
The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

Printed in the U.S.A.

speedqueen.com

Speed Queen®

© 2013 Alliance Laundry Systems LLC AC13-0002